

REI-10S6S-4B5000-H1181
Incremental Encoder
Industrial Line



Technical data

Type	REI-10S6S-4B5000-H1181
ID	100010338
Measuring principle	Optical
General data	
Max. rotational speed	6000 rpm
Moment of inertia of the rotor	$1.8 \times 10^{-5} \text{ kgm}^2$
Starting torque	< 0.05 Nm
Output type	Incremental
Resolution incremental	5000 ppr
Electrical data	
Operating voltage U_B	5...30 VDC
No-load current	≤ 90 mA
Output current	≤ 20 mA
Short-circuit protection	yes
Wire break/reverse polarity protection	yes
Pulse frequency max.	300 kHz
Signal level high	min. 2.5 V
Signal level low	max. 0.5 V
Output function	RS422/TTL, invertable
Mechanical data	
Flange type	Synchro flange
Flange diameter	Ø 58 mm
Shaft Type	Solid shaft
Shaft diameter D (mm)	6
Shaft Length L [mm]	10
Shaft material	Stainless steel

Features

- Synchro flange, Ø 58 mm
- Solid shaft, Ø 6 mm × 10 mm
- Optical measuring principle
- Shaft material: stainless steel
- Protection class IP67 on housing and shaft side
- -40...+85 °C
- Max. 6000 rpm (continuous operation 3000 rpm)
- 5...30 VDC
- RS422/TTL invertible
- Pulse frequency max. 300 kHz
- M12 × 1 male connector, 8-pin
- 5000 pulses per revolution




Technical data


Housing material	Die-cast zinc
Electrical connection	Connector, M12 × 1
	8-pin
Axial shaft load	40 N
Radial shaft load	80 N
Environmental conditions	
Ambient temperature	-40...+85 °C
Vibration resistance (EN 60068-2-6)	300 m/s ² , 10...2000 Hz
Shock resistance (EN 60068-2-27)	3000 m/s ² , 6 ms
Protection class	IP67
Protection class shaft	IP67

Accessories


RCS-15-08-06	1545361
Bellows coupling, outer diameter: 15 mm, bore diameter: 8 mm/6 mm	




RCS-15-06-04	1545363
Bellows coupling, outer diameter: 15 mm, bore diameter: 6 mm/4 mm	




RA-BC-20-06-06	100048777
Bellows coupling with aluminum hub Ø 20 mm; d1 = 6 mm, d2 = 6 mm	




RA-BC-20-06-08	100048778
Bellows coupling with aluminum hub Ø 20 mm; d1 = 6 mm, d2 = 8 mm	




RA-BC-20-06-10	100048779
Bellows coupling with aluminum hub Ø 20 mm; d1 = 6 mm, d2 = 10 mm	




RA-BC-E-20-06-06	100048785
Stainless steel bellows coupling Ø 20 mm; d1 = 6 mm, d2 = 6 mm	




RA-BC-E-20-06-10	100048786
Stainless steel bellows coupling Ø 20 mm; d1 = 6 mm, d2 = 10 mm	




RA-SDC-30-06-10	100048791
Spring disc coupling Ø 30 mm; d1 = 6 mm, d2 = 10 mm	



RA-SDC-30-06-06	100048790
Spring disc coupling Ø 30 mm; d1 = 6 mm, d2 = 6 mm	




RA-HC-25-06-06	100048794
Aluminum helix coupling Ø 25 mm; d1 = 6 mm, d2 = 6 mm	





RA-HC-25-06-10

100048795



Aluminum helix coupling Ø 25 mm; d1 = 6 mm, d2 = 10 mm

Accessories

Dimension drawing	Type	ID	
	RKC8T-2/TXL	6625142	Connection cable, M12 female connector, straight, 8-pin, cable length: 2 m, jacket material: PUR, black; cULus approval
	WKC8T-2/TXL	6625145	Connection cable, M12 female connector, angled, 8-pin, cable length: 2 m, jacket material: PUR, black; cULus approval