


DT06-8S-A-25/TXL

Deutsch Connector – Connection Cable



Technical data


Type	DT06-8S-A-25/TXL
ID	100038087
Connector A	Female, Deutsch DT, Straight
Number of pins	8
Contacts	Brass, CuZn, Nickel-plated
Contact carriers	Plastic, Thermoplast, Green
Connector body	Plastic, TPU, UL 94, Black
Seal	Plastic, Silicone
Mechanical lifespan	> 100 Mating cycles
Protection class	IP67, IP69K, (plugged)
Cable	
Cable diameter	Ø 8 mm ±0.25
Cable length	25 m
Cable jacket	PUR, Black
Core insulation	PP
Core cross-section	8 x 0.75 mm²
Arrangement of strands	42 x 0.15 mm
Core colors	BN, GN, YE, GY, PK, BU, RD, WH
Electrical properties at +20 °C	
Rated voltage	48 V _{AC} /60 V _{DC}
Current	6 A
Mechanical and chemical properties	
Bending radius (flexible use)	≥ 12 x Ø
Bending cycles	≥ 2 million
Admissible acceleration	max. 10 m/s²
Admissible traversing speed	1.67 m/s
Ambient temperature (fixed)	-40...+80 °C

Features



- Deutsch connector DT06, straight, 8-pin
- Jacket material: TPE-U (PUR)
- Jacket color: black, similar to RAL 7021
- Suitable for drag chain use
- Flame retardant
- Halogen free acc. to DIN VDE 0472 part 815
- RoHS compliant
- Protection classes IP67 and IP69K
- Cable length: 25 m

Contact assignment



Circuit Diagram

1	GN
2	BN
3	WH
4	PK
5	GY
6	YE
7	BU
8	RD

Technical data

Ambient temperature (mobile)	-25...+80 °C
------------------------------	--------------
