


DT06-2S-A-15-DT04-2P-A/TXL

Deutsch Connector – Extension Cable

Features

- Deutsch connector DT06, straight, 2-pin
- Jacket material: TPE-U (PUR)
- Jacket color: black, similar to RAL 7021
- Suitable for drag chain use
- Flame retardant
- Halogen free acc. to DIN VDE 0472 part 815
- RoHS compliant
- Protection classes IP67 and IP69K
- Cable length: 15 m

Contact assignment



Technical data

Type	DT06-2S-A-15-DT04-2P-A/TXL
ID	100046075
Connector A	Female, Deutsch DT, Straight
Number of pins	2
Contacts	Brass, CuZn, Nickel-plated
Contact carriers	Plastic, Thermoplast, Green
Connector body	Plastic, TPU, UL 94, Black
Seal	Plastic, Silicone
Mechanical lifespan	> 100 Mating cycles
Protection class	IP67, IP69K, (plugged)
Connector B	Male, Deutsch DT, Straight
Contacts	Brass, CuZn, Nickel plated
Contact carriers	Plastic, TPU, Green
Connector body	Plastic, TPU, UL 94, Black
Seal	Plastic, Silikon
Mechanical life	> 100 Mating cycles
Pollution degree	3
Protection class	IP67, IP69K, (Plugged)
Cable	
Cable diameter	Ø 5 mm ±0.15
Cable length	15 m
Cable jacket	PUR, Black
Core insulation	PP
Core cross-section	2 x 0.75 mm²
Arrangement of strands	42 x 0.15 mm
Core colors	BN, BU

Technical data

Electrical properties at +20 °C	
Rated voltage	230 V
Current	8 A
Mechanical and chemical properties	
Bending radius (stationary installation)	$\geq 5 \times \varnothing$
Bending radius (flexible use)	$\geq 10 \times \varnothing$
Bending cycles	≥ 4 million
Admissible acceleration	max. 10 m/s ²
Admissible traversing speed	3.33 m/s
Ambient temperature (fixed)	-40...+80 °C
Ambient temperature (mobile)	-25...+80 °C