

Technical data

Environmental conditions


Ambient temperature	-40...+80 °C
Vibration resistance (EN 60068-2-6)	10 g (100 m/s²), 55...2000 Hz
Shock resistance (EN 60068-2-27)	250 g (2500 m/s²), 6 ms
Protection class	IP67
Protection class shaft	IP67
MTTF	19 years

Accessories

RA-BC-20-06-10

100048779


Bellows coupling with aluminum hub
 $\varnothing$ 20 mm; d1 = 6 mm, d2 = 10 mm



RA-BC-20-08-10

100048781


Bellows coupling with aluminum hub
 $\varnothing$ 20 mm; d1 = 8 mm, d2 = 10 mm



RA-BC-20-10-10

100048782


Bellows coupling with aluminum hub
 $\varnothing$ 20 mm; d1 = 10 mm, d2 = 10 mm



RA-BC-20-10-12

100048783


Bellows coupling with aluminum hub
 $\varnothing$ 20 mm; d1 = 10 mm, d2 = 12 mm



RA-BC-E-20-06-10

100048786


Stainless steel bellows coupling $\varnothing$
20 mm; d1 = 6 mm, d2 = 10 mm



RA-BC-E-20-10-10

100048787


Stainless steel bellows coupling $\varnothing$
20 mm; d1 = 10 mm, d2 = 10 mm



RA-BC-E-20-10-12

100048788


Stainless steel bellows coupling $\varnothing$
20 mm; d1 = 10 mm, d2 = 12 mm



RA-SDC-30-10-10

100048792


Spring disc coupling $\varnothing$ 30 mm; d1 =
10 mm, d2 = 10 mm



RA-SDC-30-10-12

100048793


Spring disc coupling $\varnothing$ 30 mm; d1 =
10 mm, d2 = 12 mm



RA-HC-25-10-10

100048796


Aluminum helix coupling $\varnothing$ 25 mm; d1
= 10 mm, d2 = 10 mm



RA-HC-25-10-12

100048797

Aluminum helix coupling $\varnothing$ 25 mm; d1
= 10 mm, d2 = 12 mm



Accessories

Dimension drawing	Type	ID	
	RSSD-RSSD-4422-2M	6635150	Cable for Industrial Ethernet, M12 male connector, D-coded, straight to M12 male connector, D-coded, straight, cable length: 2 m, jacket material: PUR, green
	WSSD-WSSD-4422-2M	6635188	Cable for Industrial Ethernet, M12 male connector, D-coded, angled to M12 male connector, D-coded, angled, cable length: 2 m, jacket material: PUR, green
	RSSD-RJ45S-4422-2M	6635170	Cable for Industrial Ethernet, M12 male connector, D-coded, straight to RJ45 male connector, straight, cable length: 2 m, jacket material: PUR, green
	RSSD-RJ45S-4422-7M	6635579	Cable for Industrial Ethernet, M12 male connector, D-coded, straight to RJ45 male connector, straight, cable length: 2 m, jacket material: PUR, green
	RSSD-RJ45S-4422-8M	6635538	Cable for Industrial Ethernet, M12 male connector, D-coded, straight to RJ45 male connector, straight, cable length: 2 m, jacket material: PUR, green
	RKC4.4T-2/TXL	6625503	Connection cable, M12 female connector, straight, 4-pin, cable length: 2 m, jacket material: PUR, black; cULus approval
	WKC4.4T-2/TXL	6625515	Connection cable, M12 female connector, angled, 4-pin, cable length: 2 m, jacket material: PUR, black; cULus approval