


TL50HYW

LED Signal Light – High-intensity Tower Light




Technical data

Type	TL50HYW
ID	3044720
Signal and display data	
Purpose	LED indicator light
Function	Tower light
Light type	Yellow White
Dimmable	No
Features of color 1	Yellow, Permanently on, 23 lm
Features of color 2	White, Permanently on, 50 lm
Electrical data	
Operating voltage U_B	18...30 VDC
DC rated operating current I_e	≤ 100 mA
Operating voltage U_B	21...27 VAC
AC rated operational current	≤ 100 mA
Max. current consumption per color	100 mA
Input type	Bipolar (PNP/NPN)
Response time typical	< 10 ms
Mechanical data	
Cascadable	No
Design	Smooth barrel, TL50H
Dimensions	Ø 50 x 120.8 mm
Housing material	Plastic, ABS, Black
Window material	Polycarbonate, diffuse
Electrical connection	Cable, 2 m, PVC
Number of cores	4
Ambient temperature	-40...+50 °C

Features

- Plastic housing, black
- EMI and RFI immune
- Protection class IP67
- Cable 2 m
- Colors: Yellow (COL 1) / White (COL 2)
- Operating voltage: 18...30 VDC or 24 VAC with 45 mA per LED color
- Inputs: PNP/NPN

Wiring diagram



Functional principle

The TL50H tower lights, in the high-brightness version, provide highly visible status indicators and a clear user guidance within the entire system. They can be assembled from varicolored LEDs and are available with or without beeper. You can mount them directly on machines, in the cabinet or in monitoring locations of production lines.

The wiring diagram shows a PNP pin assignment.

There are 5 colors available, blue (B), green (G), red (R), yellow (Y) and white (W), which specify the light sequence from bottom to top in the type code of the tower light. Example: TL50GYRQ, colors green, yellow and red arranged from bottom to top.

