


PVA225P6R

Pick-to-Light – Placement Sensor

Light Grid




Features

- Scan field Y: 225 mm
- Total height 266.4 mm
- 10-beam system, beam spacing 25 mm
- Receiver
- Range max. 2 m
- Light / Dark operation
- Selectable frequency as protection against crosstalk
- Operating voltage 12...30 VDC
- PNP switching output of the receiver
- Input of operation request light +24 VDC
- Protection class IP62

Technical data

Type	PVA225P6R
ID	3050789
Signal and display data	
Purpose	Pick-to-Light
Function	Opposed mode sensor
Max. range	2000 mm
Scan field	225 mm
Number of beams	10
Optical resolution	25 mm
Switch Function	Momentary
Features of color 1	Green, Can be set via DIP switches
Electrical data	
Operating voltage U_B	12...30 VDC
Max. current consumption per color	62 mA
Output function	NO/NC, PNP
Input type	Bipolar (PNP/NPN)
Response time typical	< 40 ms
Mechanical data	
Design	Rectangular, PVA
Dimensions	266.4 x 30 x 15 mm
Housing material	Metal, AL, Black
Window material	Acrylic, clear
Electrical connection	Cable, 2 m, PVC
Number of cores	4
Ambient temperature	0...+50 °C

Wiring diagram



Functional principle


This light screen used for fault detection and assembly sequences, has good visible job lights at the emitter and the receiver, guiding the operator through the picking sequence. Missing parts and incorrect assembly are thus avoided. A control unit issues the work sequence and indicates the next work step after receiving feedback from the light screen. Misspick is immediately detected and indicated by a red flashing light.

Technical data

Protection class	IP62
Tests/approvals	
Approvals	CE, cURus


Accessories

SMBPVA10 3056809




Mounting bracket, for PVA225, cold-rolled steel, cut-out for DIP switch block

SMBPVA10A 3062447




Mounting bracket, for PVA225, cold-rolled steel, cut-out for DIP switch block, protection for light

SMBPVA10AB 3070806



Mounting bracket, for PVA225, cold-rolled steel, no cut-out for DIP switch block, protection for light

SMBPVA1 3056884



Mounting bracket, for PVA and PVD, stainless steel; set consisting of two brackets and screws