


# K50APLPGREQ

## Pick-to-Light – Placement Sensor



### Retroreflective Sensor with Polarizing Filter



#### Features

- Protection class IP67
- Male M12 x 1, 4-pin
- Job light: green
- Mispick: red
- Actuation: not signalled
- Operating voltage 12...30 VDC
- PNP switching
- NO contact

#### Wiring diagram



#### Functional principle

The K50 pick-and-place sensor is suitable for many mounting and component placement applications. The green work light or other signal lights are reflected perfectly by the entire dome (depending on the version). The transistor output can be easily connected to a system control, which is programmed for a special task sequence. The work light of the sensor is located in or next to every bin at the operator's workstation and indicates: 1. The bins with the components to be picked up for a particular work step and 2. the sequence in which the components have to be picked up. If the operator removes a part from the bin, the K50 detects the hand in the bin and sends a signal to the control unit. The system then checks if the correct component has been picked up and – depending on the configuration – switches the corresponding work light off and the next one on, according to the assembly sequence. The work sequence control leads to increased efficiency, improved quality control and reduces rework and testing expenses. The term work light therefore refers to the visual indicator of the bin from which a part should be removed next. The actuation indicator confirms the removal with a different color. The mispick indicator illuminates if a bin

#### Technical data

|                                    |                                    |
|------------------------------------|------------------------------------|
| Type                               | K50APLPGREQ                        |
| ID                                 | 3076284                            |
| <b>Signal and display data</b>     |                                    |
| Purpose                            | Pick-to-Light                      |
| Function                           | Retroreflective Sensor             |
| Max. range                         | 2000 mm                            |
| Light type                         | Red                                |
| Number of beams                    | 1                                  |
| Switch Function                    | Momentary                          |
| Features of color 1                | Green, Permanently on              |
| Features of color 2                | Red                                |
| Special features                   | I/O module-compatible<br>Wash down |
| <b>Electrical data</b>             |                                    |
| Operating voltage $U_B$            | 12...30 VDC                        |
| DC rated operating current $I_a$   | ≤ 150 mA                           |
| Max. current consumption per color | 75 mA                              |
| Output function                    | NO contact, PNP                    |
| Input type                         | PNP                                |
| Response time typical              | < 3 ms                             |
| <b>Mechanical data</b>             |                                    |
| Design                             | Dome, K50                          |
| Dimensions                         | Ø 50 x 67.8 mm                     |
| Housing material                   | Plastic, PC, Black                 |
| Window material                    | Polycarbonate, diffuse             |

Technical data

|                       |                                           |
|-----------------------|-------------------------------------------|
| Electrical connection | Connector, M12 × 1, PVC                   |
| Number of cores       | 4                                         |
| Ambient temperature   | -40...+50 °C                              |
| Relative humidity     | 0...90 %                                  |
| Protection class      | IP67<br>IP69                              |
| Tests/approvals       |                                           |
| MTTF                  | 146 years acc. to SN 29500 (Ed. 99) 40 °C |
| Approvals             | CE, cULus listed                          |

was reached into when the work light was not set.

Accessories

SMB30A3032723

Mounting bracket, rectangular, stainless steel, for sensors with 30mm thread

SMB30SC3052521

Mounting bracket, PBT black, for sensors with 30 mm thread, rotatable

SMB30FA3074005

Montagewinkel; Werkstoff VA 1.4401

Accessories

Dimension drawing


Type

ID



RKC4.4T-2/TEL

6625013

Connection cable, M12 female connector, straight, 4-pin, cable length: 2 m, jacket material: PVC, black; cULus approval

| Dimension drawing                                                                 | Type          | ID      |                                                                                                                       |
|-----------------------------------------------------------------------------------|---------------|---------|-----------------------------------------------------------------------------------------------------------------------|
|  | WKC4.4T-2/TEL | 6625025 | Connection cable, M12 female connector, angled, 4-pin, cable length: 2 m, jacket material: PVC, black; cULus approval |

Accessories

| Dimension drawing                                                                 | Type        | ID      |                                                                                                                              |
|-----------------------------------------------------------------------------------|-------------|---------|------------------------------------------------------------------------------------------------------------------------------|
|  | BRT-51X51BM | 3071791 | Rectangular reflector, reflection coefficient 2.0, material acrylic, ambient temperature -20 ... +60 °C, microprism geometry |
|  | BRT-84      | 3058979 | Round reflector, reflection coefficient 1.4, material acrylic, ambient temperature -20 ... +60 °C                            |