



Photoelectric Sensor Opposed Mode Sensor (Receiver) Q20PRLQ





- Cable with male end, PVC, M8 × 1, 4-pin, 150 mm
- Protection class IP67
- LED, all-round visible
- Operating voltage: 10...30 VDC
- PNP switching output, changeover

Wiring Diagram




Functional principle

Opposed mode sensors consist of an emitter and a receiver. They are installed in such a way that the emitted light is aimed directly at the receiver. When an object interrupts or weakens the light beam, a switching operation is triggered. Opposed mode sensors are the most reliable photoelectric sensors for any application that requires the detection of opaque objects. High light/dark contrast and very high excess gain are typical of this operating mode and enable operation over long distances and under difficult conditions.

Excess Gain Curve

Туре	Q20PRLQ	
ID	3078282	
Optical data		
Function	Opposed mode sensor	
Operating mode	Receiver	
Range	020000 mm	
Electrical data		
Operating voltage U _B	1030 VDC	
Residual ripple	< 10 % U _{ss}	
DC rated operating current I.	≤ 100 mA	
No-load current I _o	≤ 18 mA	
Reverse polarity protection	yes	
Output function	Complementary contact, PNP	
Switching frequency	≤ 600 Hz	
Readiness delay	≤ 100 ms	
Response time typical	< 1 ms	
Mechanical data		
Design	Rectangular, Q20	
Housing material	Plastic, Thermoplastic material	
Lens	plastic, Acrylic	
Electrical connection	Cable with connector, M8 × 1, 0.15 m, PVC	
Number of cores	4	
Ambient temperature	-20+60 °C	
Protection class	IP67	
Power-on indication	LED, Green	
Switching state	LED, Yellow	
Error indication	LED, green, Flashing	
Excess gain indication	LED, yellow, flashing	
Exocos gain indication	LLD, yellow, liability	
Tests/approvals		
Approvals	CE	







Accessories

Type code	Ident no.		Dimension drawing
SMBQ20H	3079041	Mounting bracket, stainless steel, horizontally mounted, for Q20	3,4 x 10.3 30 15,7 20 3,4 x 9,4
SMBQ20L	3079040	Mounting bracket, stainless steel, rectangular, for Q20	
			3,4 x 8,3 40 40 29 3,4 x 9,4
SMBQ20LV	3079042	Mounting bracket, stainless steel, rectangular, for Q20	
			3,4 x 9,4 31,2 36 16,2
SMBQ20U	3079043	Protective housing, stainless steel, for Q20	
			3,2 x 12,6 (2x) 38,5 0 25 34