


WLB92X550PB LED Linear Light – In the Metal Housing



Technical data


continuation Linear White Solor temperature 4700 minous flux lumen 3130	work light ar light e
Irpose LED Inction Linea Other type White Other temperature 4700 Iminous flux lumen 3130	e+5300 K
conction Linear White State of the State of	e+5300 K
pht type White blor temperature 4700 minous flux lumen 3130	e +5300 K
plor temperature 4700 minous flux lumen 3130	+5300 K
minous flux lumen 3130	
	. 1
mmable Pote	ım
	ntiometer
eatures of color 1 White	e, Permanently on, 3510 lm
ectrical data	
perating voltage U _B 21.6.	26.4 VDC
C rated operating current I _e ≤ 14	50 mA
echanical data	
ascadable No	
esign Rect	angular, WLB92
mensions 665	x 97 x 104 mm
ousing material Meta	I, AL, Anodized
indow material Polye	carbonate, diffuse
ectrical connection Cabl	e, 2 m, PVC
umber of cores 2	
nbient temperature -40	.+70 °C
otection class IP40	
ests/approvals	
pprovals CE	



Features

- ■Light beam: 550 mm
- Operating voltage: 24 VDC (±10%)
- ■Protection class: IP50
- Color: White
- ■Cable, 2 m
- ■Built-in ON/OFF switch
- Integrated rotary switch for continuous dimming of the light output (0% 100%)

Wiring diagram



Functional principle


The WLB92 LED linear light is designed for multi-purpose use, is powered by 24 VDC and convinces by its robust metal housing and shatter-proof window material. With the built-in toggle switch, the light can be switched on or off and also fully dimmed, 0%-100%, by the rotary switch. The color temperature lies in the range of daylight, between 5,000 and 10,000 Kelvin. With a lifetime of 50,000 hours and very energy efficient LEDs, this a cost-saving and environmentally friendly alternative to conventional fluorescent lamps. This linear light is available in two lengths and more than twice as bright as the known WLB32 LED light.



Accessories

LMBWLB92 3093567


Snap bracket for WLB92 work light, included in the WLB92 scope of delivery



LMBWLB92CLIP

3093568

Snap bracket for WLB92 linear light



LMBWLB92HK5

3093569


Pendant mounting bracket for WLB92



LMBWLB92S

3093570

Mounting bracket for front side mounting of the WLB92



LMBWLB92RAS

3093571

Pivoting mounting bracket for WLB92 line light

