


K50LWOXN

LED Signal Light – Beacon




Technical data

Type	K50LWOXN
ID	3096312
Signal and display data	
Purpose	LED indicator light
Function	Spotlight
Light type	White Orange
Dimmable	No
Features of color 1	White, Permanently on
Features of color 2	Orange
Special features	Wash down
Electrical data	
Max. current consumption per color	40 mA
Input type	minus-schaltend
Response time typical	< 1 ms
Mechanical data	
Cascadable	No
Design	Dome, K50L
Dimensions	Ø 50 x 58 mm
Housing material	Plastic, PC, Black
Window material	Polycarbonate, diffuse
Electrical connection	Cable, 2 m, PVC
Number of cores	4
Ambient temperature	-40...+50 °C
Relative humidity	0...90 %
Protection class	IP67 IP69

Features

- LED all-round visible
- Individually controllable
- Screw-in thread M30x1.5
- Protection class IP67
- Multicolor: White (COL 1) / Orange (COL 2)
- Cable 2 m
- Operating voltage 18...30 VDC



Wiring diagram



Technical data

Tests/approvals	
MTTF	249 years acc. to SN 29500 (Ed. 99) 40 °C
Approvals	CE, UL listed

Accessories

SMB30A	3032723	SMB30SC	3052521
	Mounting bracket, rectangular, stainless steel, for sensors with 30mm thread		Mounting bracket, PBT black, for sensors with 30 mm thread, rotatable