


LED Signal Light Tower Light TL50TRAOSQ



Type	TL50TRAOSQ
ID	3800720

Signal and display data	
Purpose	LED indicator light
Function	Tower light
Light type	Turquoise Red
Dimmable	No
Features of color 1	Turquoise, Permanently on, 5.5 lm
Features of color 2	Red, Permanently on, 7.5 lm
Acoustic signal	Continuous tone, 99dB


Electrical data	
Operating voltage U_a	18...30 VDC
DC rated operating current I_a	≤ 45 mA
Operating voltage U_a	21...27VAC
Max. current consumption per color	45 mA
Max. current consumption of beeper	45 mA
Input type	Bipolar (PNP/NPN)
Response time typical	< 10 ms

Mechanical data	
Cascadable	No
Design	Smooth barrel, TL50
Dimensions	$\varnothing 50 \times 197.3$ mm
Housing material	Plastic, ABS, Black
Window material	Polycarbonate, diffuse
Electrical connection	Connector, M12 $\times$ 1, PVC
Number of cores	4
Ambient temperature	-20...+50 °C
Relative humidity	0...95%
Protection class	IP67

Tests/approvals	
Approvals	CE, UL listed

- Plastic housing, black
- EMI and RFI immune
- Protection class IP67
- M12 x 1 male
- Colors: Turquoise (COL 1) / Red (COL 2)
- Operating voltage: 18...30 VDC or 24 VAC with 45 mA per LED color
- Inputs: PNP/NPN
- Beeper: Omnidirectional, sealed, continuous tone max. 99 dB

Wiring Diagram



Functional principle

The TL50 tower lights provide highly visible status indicators and a clear user guidance within the entire system. They can be assembled from varicolored LEDs and are available with or without beeper. You can mount them directly on machines, in the cabinet or in locations to be monitored within the production lines.

The wiring diagram shows a PNP pin assignment.

There are 10 colors available blue (B), green (G), red (R), yellow (Y), white (W), turquoise (T), orange (O), violet (V), sky blue (S) and magenta (M), which specify the light sequence from bottom to top in the type code of the tower light. Example: TL50GYRQ, colors

green, yellow and red arranged from bottom
to top.