



LED Signal Light Tower Light TL50HBRGAOSCQ



- Plastic housing, gray
- EMI and RFI immune
- Protection class IP67
- M12 × 1 male connector
- Colors: Blue (COL 1) / Red (COL 2) / Green (COL 3)
- Operating voltage: 18...30 VDC or 24 VAC with 45 mA per LED color
- Inputs: PNP/NPN
- Beeper: Omnidirectional, sealed, continuous tone max. 99 dB

Wiring Diagram



Functional principle

The TL50H tower lights, in the high-brightness version, provide highly visible status indicators and a clear user guidance within the entire system. They can be assembled from various colored LEDs and are available with or without beeper. You can mount them directly on machines, in the cabinet or in monitoring locations of production lines.

The wiring diagram shows a PNP pin assignment.

There are 5 colors available, blue (B), green (G), red (R), yellow (Y) and white (W), which specify the light sequence from bottom to top in the type code of the tower light. Example: TL50GYRQ, colors green, yellow and red arranged from bottom to top.

Type	TL50HBRGAOSCQ
ID	3801700
Signal and display data	
Purpose	LED indicator light
Function	Tower light
Light type	Blue Red Green
Dimmable	No
Features of color 1	Blue, Permanently on, 23 lm
Features of color 2	Red, Permanently on, 32 lm
Features of color 3	Green, Permanently on, 60 lm
Acoustic signal	Continuous tone, 99dB
Electrical data	
Operating voltage U_s	18...30 VDC
DC rated operating current I_s	≤ 100 mA
Operating voltage U_s	21...27VAC
Max. current consumption per color	100 mA
Max. current consumption of beeper	45 mA
Input type	Bipolar (PNP/NPN)
Response time typical	< 10 ms
Mechanical data	
Cascadable	No
Design	Smooth barrel, TL50
Dimensions	Ø 50 x 238 mm
Housing material	Plastic, ABS, Grey
Window material	Polycarbonate, diffuse
Electrical connection	Connector, M12 × 1, PVC
Number of cores	5
Ambient temperature	-20...+50 °C
Relative humidity	0...95%
Protection class	IP67
Tests/approvals	
Approvals	CE, UL listed