

# WKC12T-0.6-RSC12T/TEL

## Actuator and Sensor Cable, PVC – Extension Cable



### Technical data


|                              |                                         |
|------------------------------|-----------------------------------------|
| Type                         | WKC12T-0.6-RSC12T/TEL                   |
| ID                           | 6625356                                 |
| Connector A                  | Female, M12 × 1, Angled, A-coded        |
| Number of pins               | 12                                      |
| Contacts                     | Brass, CuZn, Gold-plated                |
| Contact carriers             | Plastic, TPU, Black                     |
| Connector body               | Plastic, TPU, Black                     |
| Coupling nut/screw           | Brass, CuZn, Nickel-plated              |
| Seal                         | Plastic, FPM/FKM                        |
| Mechanical lifespan          | > 100 Mating cycles                     |
| Pollution degree             | 3                                       |
| Protection class             | IP67, IP69K, Only in screwed condition  |
| Connector B                  | Male, M12 × 1, Straight, A-coded        |
| Number of Pins               | 12                                      |
| Contacts                     | Brass, CuZn, Gold-plated                |
| Contact carriers             | Plastic, TPU, Black                     |
| Connector body               | Plastic, TPU, Black                     |
| Coupling nut/retaining screw | Brass, CuZn, Nickel-plated              |
| Mechanical life              | > 100 Mating cycles                     |
| Pollution degree             | 3                                       |
| Protection class             | IP67, IP69K, Only when screwed together |
| Cable                        |                                         |
| Cable diameter               | Ø 5.9 mm ±0.20                          |
| Cable length                 | 0.6 m                                   |
| Cable jacket                 | PVC, Black                              |
| Core insulation              | PVC                                     |
| Core cross-section           | 12 x 0.14 mm²                           |

### Features



- Female M12, angled, 12-pin
- Male M12, straight, 12-pin
- Jacket material: PVC
- Jacket color: black
- Resistant to chemicals and oils
- Flame retardant
- Resistant to acids and alkaline solutions
- Resistant to microbes and hydrolysis
- LABS free
- Protection class: IP67, IP69K
- Cable length: 0.6 m

### Cable Cross-Section



### Contact assignment

Technical data

|                                          |                                                                |
|------------------------------------------|----------------------------------------------------------------|
| Arrangement of strands                   | 18 x 0.1 mm                                                    |
| Core colors                              | BN, WH, BU, BK, GY, PK, VT, OG, GY/<br>PK, WH/BU, WH/GY, GY/BN |
| Electrical properties at +20 °C          |                                                                |
| Rated voltage                            | 30 V                                                           |
| Test voltage                             | 2000 V                                                         |
| Current                                  | 1.5 A                                                          |
| Insulation resistance                    | > 30.5 MΩ/km                                                   |
| forward resistance                       | max. 138 Ω/km                                                  |
| Mechanical and chemical properties       |                                                                |
| Bending radius (stationary installation) | ≥ 5 x Ø                                                        |
| Bending radius (flexible use)            | ≥ 10 x Ø                                                       |
| Ambient temperature (fixed)              | -40...+105 °C                                                  |
| Ambient temperature (mobile)             | -5...+80 °C                                                    |
| Approvals                                | cULus                                                          |

Stranded Wire Colors

| Pin | DIN 47100 (old) | DIN EN 60947-5-2 (new) |
|-----|-----------------|------------------------|
| 1   | BN              | BN                     |
| 2   | BU              | WH                     |
| 3   | WH              | BU                     |
| 4   | GN              | BK                     |
| 5   | PK              | GY                     |
| 6   | YE              | PK                     |
| 7   | BK              | VT                     |
| 8   | GY              | OG                     |
| 9   | RD              | GY/PK                  |
| 10  | VT              | WH/BU                  |
| 11  | GY/PK           | WH/GY                  |
| 12  | RD/BU           | GY/BN                  |




Functional principle

Drawing shows design status including hexagon coupling nut (Production start CW11/2016).  
Wiring diagram shows contact assignment acc. to DIN EN 60947-5-2 (Production start CW16/2017).

Circuit Diagram

|    |       |    |
|----|-------|----|
| 1  | BN    | 1  |
| 2  | WH    | 2  |
| 3  | BU    | 3  |
| 4  | BK    | 4  |
| 5  | GY    | 5  |
| 6  | PK    | 6  |
| 7  | VT    | 7  |
| 8  | OG    | 8  |
| 9  | GY/PK | 9  |
| 10 | WH/BU | 10 |
| 11 | WH/GY | 11 |
| 12 | GY/BN | 12 |

Accessories

|                                                                                                                       |         |                                                                                                                                         |         |
|-----------------------------------------------------------------------------------------------------------------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------|---------|
| TORQUE-WRENCH-SET-AS                                                                                                  | 6936170 | BLANK-LABEL-FOR-CORDSETS-TEL-TXL                                                                                                        | 6936206 |
| Torque wrench set; handles with adjustable torque 0.4-1.0 Nm, torque wrench for M8 (SW9), fork wrench for M12 (SW 14) |         | Label for TEL and TXL cables, length: 18 mm, height: 4 mm, material: polycarbonate (PC), color: white, halogen-free and flame-retardant |         |
|                                      |         |                                                       |         |

Accessories

|                                                                                   |                       |           |                                                                                                                                                                            |
|-----------------------------------------------------------------------------------|-----------------------|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Dimension drawing                                                                 | Type                  | ID        |                                                                                                                                                                            |
|  | LABEL-HOLDER-FLEX-PVC | 100048170 | PVC label holder for identification of extension cables (TEL/TXL product series); for cable diameters: min. 5 mm; dimensions 4 × 18 mm; delivery unit: 50 pcs. per package |
|                                                                                   |                       |           |                                                                                                                                                                            |