



RFID Cable Standard Version
Connection Cable
WK4.5T-10/S2500




Type	WK4.5T-10/S2500
ID	6699209
Connector A	Female, M12 × 1, Angled, A-coded
Number of Pins	5
Contact carriers	Plastic, TPU, Black
Connector body	Plastic, TPU, Black
Coupling nut/screw	Brass, CuZn-Ni, Nickel-plated
Tightening torque (range)	0.6 ... 1 Nm (observe max. torque of mating connector!)
Mechanical lifespan	> 100 Mating cycles
Pollution degree	3
Protection class	IP67, IP69K, Only in screwed condition
Cable	
Cable diameter	Ø 6.9mm
Cable length	10 m m
Cable jacket	PUR, Yellow
Shielding	yes
Data cable cores	
Core cross-section	2 x 0.25 mm²
Power cable cores	
Core cross-section	2x 0.34 mm²
Core colors	Power: BN, BU Data: WH, BK
Electrical properties at +20 °C	
Rated voltage	30VV
Current	4AA
DC resistance (loop)	103 Ω/km
Nom. impedance	135 Ω
Nom. capacitance	50 pF/m

- 4-wire, AWG 24/AWG 22
- Jacket material: PUR, color: yellow
- Free from halogen and LABS
- Shielding: Aluminum foil, tinned copper braid
- Jacket diameter: 6.9 mm
- Suitable for drag chain use, oil resistant, highly flexible
- Cable UL Style 20594
- Open end
- Cable length: 10 m



Circuit Diagram



Mechanical and chemical properties	
Bending radius (flexible use)	$\geq 8 \times \varnothing$
Bending cycles	≥ 1 million
Ambient temperature range (stationary)	-40°C...+80°C°C
Ambient temperature range (In motion)	-25°C...+80°C°C

Other Features	
Qualified for drag chain use	yes
Halogen-free	yes